


33055**1991-2007 FORD ECONOLINE VAN E-150/250/350
(INCLUDING RV CUTAWAY)**


10/5/2012

GROSS LOAD CAPACITY WHEN USED AS A WEIGHT CARRYING HITCH: 5000 LBS. TRAILER WEIGHT & 500 LBS. TONGUE WEIGHT.
 GROSS LOAD CAPACITY WHEN USED AS A STRAIGHT LINE PULL: 9,000 LBS. MAX. LINE PULL.
***** DO NOT EXCEED VEHICLE MANUFACTURER'S RECOMMENDED TOWING CAPACITY. *****
 HAVING INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

| Parts List | | | |
|------------|-----|----------------|--|
| ITEM | QTY | PART NUMBER | DESCRIPTION |
| 1 | 4 | 1/2-13 x 1 3/4 | CARRIAGE BOLT |
| 2 | 4 | CM-SP6 | .250 x 1.00 x 3.00" SQUARE HOLE SPACER |
| 3 | 4 | 1/2-13 | HEX FLANGE NUT |
| 4 | 2 | 1_2 FISHWIRE | 1/2" FISHWIRE |



FINAL INSTALL VIEW



HITCH WEIGHT: 37 LBS.
 INSTALL TIME: 20 MINUTES
 INSTALL NOTES:

- DRILLING REQUIRED
- FISHWIRE HARDWARE

| TOOLS REQUIRED |
|------------------|
| 1/2" FISHWIRE |
| RATCHET |
| 1/2" SOCKET |
| TORQUE WRENCH |
| DRILL |
| 17/32" DRILL BIT |

FISHWIRE TECHNIQUE
 INSERT COILED END OF FISHWIRE TOOL THROUGH HITCH MOUNTING HOLE IN VEHICLE FRAME RAIL AND OUT THE ACCESS HOLE. PASS COILED END OF FISHWIRE THROUGH SPACER AND THREAD BOLT INTO COIL. KINK WIRE TO KEEP SPACER SEPERATE FROM BOLT AS SHOWN. PULL FISHWIRE, SPACER, AND BOLT THROUGH FRAME AND OUT MOUNTING HOLE. USE FISHWIRE TO GUIDE HITCH DURING MOUNTING AND PREVENT LOSS OF BOLT / SPACER INSIDE FRAME RAIL.

****NOTE: SOME VEHICLES MAY FISHWIRE THROUGH END OF FRAME****

INSTALLATION STEPS

1. If present, remove all plastic rivets on the front valance on the vehicle. (Return to customer)
2. Enlarge the existing front hole to 17/32".
3. Fishwire a 1/2" carriage bolt and CM-SP6 spacer into each hole as shown. (See Fishwire Technique)
4. Raise the hitch into position over the 1/2" carriage bolts and secure using the (4) 1/2" flange nuts.
5. Torque all 1/2" hardware to 110 ft-lbs.

PERIODICALLY CHECK THIS RECEIVER HITCH TO ENSURE THAT ALL FASTENERS ARE TIGHT AND THAT ALL STRUCTURAL COMPONENTS ARE SOUND.

Curt Manufacturing Inc., warrants this product to be free of defects in material and/or workmanship at the time of retail purchase by the original purchaser. If the product is found to be defective, Curt Manufacturing Inc., may repair or replace the product, at their option, when the product is returned, prepaid, with proof of purchase. Alteration to, misuse of, or improper installation of this product voids the warranty. Curt Manufacturing Inc.'s liability is limited to repair or replacement of products found to be defective, and specifically excludes liability for incidental or consequential loss or damage.