56152 HYUNDAI SANTE FE

WIRING LOCATION GUIDE GUÍA DE UBICACIÓN DEL CABLEADO IDE D'EMPLACEMENT DES FILS



MUST READ FIRST!

All steps must be followed to ensure correct function of the T-Connector. To verify proper installation once installed, test by connecting a test light or properly wired trailer.

IDEBE LEERSE PRIMERO!

Debe seguirse todos los pasos para asegurar el correcto funcionamiento del Conector-T. Para verificar la correcta instalación, pruebe conectando una luz de prueba o un remolque debidamente cableado.

À LIRE D'ABORD!

Pour assurer le bon fonctionnement du T-Connector, il faut suivre toutes les étapes. Pour vérifier que l'installation a été bien effectuée, branchez un feu de test ou une remorque correctement filetée.

9/13/2011







INSTALLATION QUESTIONS? CALL TECHNICAL SUPPORT AT 1-800-798-0813

English

- 1. Locate the vehicles factory tow harness connector's they will be located under the vehicle (A). Remove the protective caps (B). Insert the ends into there mating connectors. Make sure they are fully inserted with locking tabs in place (C).
- 2.Adhere the black converter box to the underside of the vehicle in a secure out of the way location using the double sided tape provided. Find a flat, clean surface that is out of the path of road spray from the tires.
- 3. Route the 4-flat to the center of the vehicle's bumper and secure using cable ties provided.
- 4. Insert the 10 AMP fuse provided into the inline fuse holder to complete the install.

WARNING:

Mount converter module inside the tow vehicle or in a protected area similar to a vehicle interior. Failure to mount the module in a protected area can cause loss of warranty, product failure including lamp malfunction, overheating and potential fire.

IMPORTANT: Battery connection must be fuse protected, 10 amp max. Exceeding the product rating can cause loss of warranty, overheating and potential fire. Do not exceed lower of tow vehicle lamp load rating or:

Signal circuits – 3.0 amps per side Tail / Running Lights – 6.0 amps total

Check vehicle owner's manual or contact vehicle manufacturer for more information.